2004 Author Index

Abu-Serriah, M.	Mechanical testing of recombinant human bone morphogenetic protein-7 regenerated bone in sheep mandibles	381–388
An, K-N.	Muscle forces analysis in the shoulder mechanism during wheelchair propulsion	213–221
An, K-N.	A kinematic method to calculate the workspace of the trapeziometacarpal joint	143–149
Andriacchi, T. P.	Sensitivity of finite helical axis parameters to temporally varying realistic motion utilizing an idealized knee model	89–100
Artola, A.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Astephen, J. L.	A multivariate gait data analysis technique: application to knee osteoarthritis	271–279
Ayoub, A. F.	Mechanical testing of recombinant human bone morphogenetic protein-7 regenerated bone in sheep mandibles	381–388
Bader, D. L.	An investigation into the effects of the hierarchical structure of tendon fascicles on micromechanical properties	109–119
Bader, R.	A novel test method for evaluation of the abrasive wear behaviour of total hip stems at the interface between implant surface and bone cement	223–230
Baek, N-K.	Frictional resistance characteristics of a capsule inside the intestine for microendoscope design	193–201
Baleani, M.	A procedure and criterion for bone cement fracture toughness testing	445–450
Barbenel, J. C.	Mechanical testing of recombinant human bone morphogenetic protein-7 regenerated bone in sheep mandibles	381–388
Baroud, G.	A finite element rheological model for polymethylmethacrylate: analysis of the cement delivery in vertebroplasty	331–338
Bereiter, H.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Berge, J. S.	Modelling the effect of prosthetic feet and shoes on the heel – ground contact force in amputee gate	173–182
Bersee, H. E. N.	Effect of joint conformity on glenoid component fixation in total shoulder arthroplasty	339–347
Beverland, D. E.	Assessment of cement introduction and pressurization techniques	11–25
Bohez, E. L. J.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84
Brett, P. N.	A flexible digit with tactile feedback for invasive clinical applications	151–157
Buchanan, F. J.	Degradation of poly-L-lactide: Part 1: *in vitro* and *in vivo* physiological temperature degradation	307–319
Buchanan, F. J.	Degradation of poly-L-lactide: Part 2: increased temperature accelerated degradation	321–330
Cavanagh, A. G.	A machine for the preliminary investigation of design features influencing the wear behaviour of knee prostheses	51–62
Chang, W-T.	Creative mechanism design for a prosthetic hand	451–459
Chao, E. Y.	*In vitro* characterization of the relationship between the Q-angle and the lateral component of the quadriceps force	63–67
Charanya, G.	Effect of foot sole hardness, thickness and footwear on foot pressure distribution parameters in diabetic neuropathy	431–443
Chen, Q-S.	A kinematic method to calculate the workspace of the trapeziometacarpal joint	143–149
Cho, C. H.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Chong, A.	Strain rate effect on the failure properties of tendons	203–206
Chou, S. M.	Strain rate effect on the failure properties of tendons	203–206
Clift, S. E.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Cooney, W. P.	A kinematic method to calculate the workspace of the trapeziometacarpal joint	143–149
Cosgarea, A. J.	*In vitro* characterization of the relationship between the Q-angle and the lateral component of the quadriceps force	63–67
Crupi, V.	Numerical analysis of bone adaptation around an oral implant due to overload stress	407–415
Delgado, J. A.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Deluzio, K. J.	A multivariate gait data analysis technique: application to knee osteoarthritis	271–279
Dickson, G. R.	Degradation of poly-L-lactide: Part 1: *in vitro* and *in vivo* physiological temperature degradation	307–319
Dickson, G. R.	Degradation of poly-L-lactide: Part 2: increased temperature accelerated degradation	321–330
Dong, R. G.	Elimination of the friction effects in unconfined compression tests of biomaterials and soft tissues	35–40
Dunne, N. J.	Assessment of cement introduction and pressurization techniques	11–25
Elias, J. J.	*In vitro* characterization of the relationship between the Q-angle and the lateral component of the quadriceps force	63–67
Erdman, A. G.	Sensitivity of finite helical axis parameters to temporally varying realistic motion utilizing an idealized knee model	89–100
Farrar, D. F.	Degradation of poly-L-lactide: Part 2: increased temperature accelerated degradation	321–330
Flivik, G.	A comparison of structural and mechanical properties in cancellous bone from the femoral head and acetabulum	425–429
Giddings, G. E. B.	A method for measuring vertical forces applied to the upper limb during sit-to-stand	461–465

© IMechE 2003

Giddins, G. E. B.	A kinematic model of the wrist based on maximization of joint contact area	349–359
Gill, F. J.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Ginebra, M. P.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Goñi, I.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Grifliths, M. V.	A flexible digit with tactile feedback for invasive clinical applications	151–157
Grigoris, P.	Steady-state elastohydrodynamic lubrication analysis of a metal-on-metal hip implant employing a metallic cup with an ultra-high molecular weight polyethylene backing	261–270
Guandalini, L.	A procedure and criterion for bone cement fracture toughness testing	445–450
Guglielmino, E.	Numerical analysis of bone adaptation around an oral implant due to overload stress	407–415
Gupta, S.	Development and experimental validation of a three-dimensional finite element model of the human scapula	127–142
Gurruchaga, M.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Harrison, A. J. L.	The application of force-sensing resistor sensors for measuring forces developed by the human hand	121–126
Hayeward, G.	Modelling the bioelectric behaviour of halo pin – patient structures during magnetic resonance imaging	159–165
Hertig, D.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Hirt, F.	Steady-state elastohydrodynamic lubrication analysis of a metal-on-metal hip implant employing a metallic cup with an ultra-high molecular weight polyethylene backing	261–270
Holzwarth, U.	A novel test method for evaluation of the abrasive wear behaviour of total hip stems at the interface between implant surface and bone cement	223–230
Hoult, S.	The application of force-sensing resistor sensors for measuring forces developed by the human hand	121–126
Howie, C. R.	The effect of acetabular cup size on the short-term stability of revision hip arthroplasty: a finite element investigation	239–249
Hwa, H. J.	Could the intraosseous fluid in cancellous bone bear external load significantly within the elastic range?	375–379
Iwamoto, Y.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Jagatia, M.	Analysis of elastohydrodynamic lubrication in McKee–Farrar metal-on-metal hip joint replacement	27–34
Jin, Z. M.	Analysis of elastohydrodynamic lubrication in McKee–Farrar metal-on-metal hip joint replacement	27–34
Jin, Z. M.	Prediction of scratch resistance of cobalt chromium alloy bearing surface, articulating against ultra-high molecular weight polyethylene, due to third body wear particles	41–50
Jin, Z. M.	Steady-state elastohydrodynamic lubrication analysis of a metal-on-metal hip implant employing a metallic cup with an ultra-high molecular weight polyethylene backing	261–270
Jun, Z. M.	A general elastohydrodynamic lubrication analysis of artificial hip joints employing a compliant layered socket under steady state rotation	283–291
Jin, Z. M.	Contact mechanics analysis of metal-on-metal hip resurfacing prostheses	293–305
Johnson, T. S.	Sensitivity of finite helical axis parameters to temporally varying realistic motion utilizing an idealized knee model	89–100
Juliusson, R.	A comparison of structural and mechanical properties in cancellous bone from the femoral head and acetabulum	425–429
Kaptein, B. L.	Development and experimental validation of a three-dimensional finite element model of the human scapula	127–142
Kaptein, B. L.	Evaluation of three pose estimation algorithms for model-based Roentgen stereophotogrammetric analysis	231–238
Kaufman, K. R.	A kinematic method to calculate the workspace of the trapeziometacarpal joint	143–149
Kawano, T.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Kim, D-E.	Frictional resistance characteristics of a capsule inside the intestine for microendoscope design	193–201
Klute, G. K.	Modelling the effect of prosthetic feet and shoes on the heel – ground contact force in amputee gate	173–182
Kontaxis, A.	Mechanical testing of recombinant human bone morphogenetic protein-7 regenerated bone in sheep mandibles	381–388
Kumagias, M.	*In vitro* characterization of the relationship between the Q-angle and the lateral component of the quadriceps force	63–67
Kuo, L-C.	A kinematic method to calculate the workspace of the trapeziometacarpal joint	143–149
La Rosa, G.	Numerical analysis of bone adaptation around an oral implant due to overload stress	407–415
Lee, D. A.	An investigation into the effects of the hierarchical structure of tendon fascicles on micromechanical properties	109–119
Lim, B. H.	Strain rate effect on the failure properties of tendons	203–206
Lin, H-T.	Muscle forces analysis in the shoulder mechanism during wheelchair propulsion	213–221
Liu, F.	Steady-state elastohydrodynamic lubrication analysis of a metal-on-metal hip implant employing a metallic cup with an ultra-high molecular weight polyethylene backing	261–270
Liu, F.	A general elastohydrodynamic lubrication analysis of artificial hip joints employing a compliant layered socket under steady state rotation	283–291
Lucchinetti, E.	Prediction of elasticity constants in small biomaterial samples such as bone. A comparison between classical optimization techniques and identification with artificial neural networks	389–405
Ma, X.	A flexible digit with tactile feedback for invasive clinical applications	151–157
Mahaisavariya, B.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84
Manero, J. M.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Mattessich, S. M.	*In vitro* characterization of the relationship between the Q-angle and the lateral component of the quadriceps force	63–67
McGloughlin, T. M.	A machine for the preliminary investigation of design features influencing the wear behaviour of knee prostheses	51–62

© IMechE 2003

Miles, A. W.	A kinematic model of the wrist based on maximization of joint contact area	349–359
Miles, A. W.	A method for measuring vertical forces applied to the upper limb during sit-to-stand	461–465
Mirghany, M.	Prediction of scratch resistance of cobalt chromium alloy bearing surface, articulating against ultra-high molecular weight polyethylene, due to third body wear particles	41–50
Mittelmeier, W.	A novel test method for evaluation of the abrasive wear behaviour of total hip stems at the interface between implant surface and bone cement	223–230
Miura, H.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Mizuno, Y.	*In vitro* characterization of the relationship between the Q-angle and the lateral component of the quadriceps force	63–67
Morejon, L.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Mullineux, G.	A kinematic model of the wrist based on maximization of joint contact area	349–359
Murakami, T.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Murphy, D. M.	A machine for the preliminary investigation of design features influencing the wear behaviour of knee prostheses	51–62
Narayanamurthy, V. B.	Effect of foot sole hardness, thickness and footwear on foot pressure distribution parameters in diabetic neuropathy	431–443
Ng, H-W.	Prediction of inter-segment stability and osteophyte formation on the multi-segment C2–C7 after unilateral and bilateral facetectomy	183–191
Ng, B. H.	Strain rate effect on the failure properties of tendons	203–206
Nikovonas, A.	The application of force-sensing resistor sensors for measuring forces developed by the human hand	121–126
Odgaard, A.	A comparison of structural and mechanical properties in cancellous bone from the femoral head and acetabulum	425–429
Oosterom, R.	Effect of joint conformity on glenoid component fixation in total shoulder arthroplasty	339–347
Oris, P.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84
Orr, J. F.	Assessment of cement introduction and pressurization techniques	11–25
Orr, J. F.	Degradation of poly-L-lactide: Part 1: *in vitro* and *in vivo* physiological temperature degradation	307–319
Orr, J. F.	Degradation of poly-L-lactide: Part 2: increased temperature accelerated degradation	321–330
Pankaj	The effect of acetabular cup size on the short-term stability of revision hip arthroplasty: a finite element investigation	239–249
Parivalavan, R.	Effect of foot sole hardness, thickness and footwear on foot pressure distribution parameters in diabetic neuropathy	431–443
Paril, K. M.	Effect of foot sole hardness, thickness and footwear on foot pressure distribution parameters in diabetic neuropathy	431–443
Phillips, A. T. M.	The effect of acetabular cup size on the short-term stability of revision hip arthroplasty: a finite element investigation	239–249
Planell, J. A.	Propagation of fatigue cracks in acrylic bone cements containing different radiopaque agents	167–172
Ploeg, H.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Reiber, J. H. C.	Evaluation of three pose estimation algorithms for model-based Roentgen stereophotogrammetric analysis	231–238
Rieker, C.	Steady-state elastohydrodynamic lubrication analysis of a metal-on-metal hip implant employing a metallic cup with an ultra-high molecular weight polyethylene backing	261–270
Rozing, P. M.	Evaluation of three pose estimation algorithms for model-based Roentgen stereophotogrammetric analysis	231–238
Rozing, P. M.	Effect of joint conformity on glenoid component fixation in total shoulder arthroplasty	339–347
Runciman, R. J.	Modelling the bioelectric behaviour of halo pin – patient structures during magnetic resonance imaging	159–165
Ryd, L.	A comparison of structural and mechanical properties in cancellous bone from the femoral head and acetabulum	425–429
Saari, A.	Modelling the bioelectric behaviour of halo pin – patient structures during magnetic resonance imaging	159–165
Saeker, B.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84
Sakai, N.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Sammut, D.	The application of force-sensing resistor sensors for measuring forces developed by the human hand	121–126
Sawae, Y.	Elasto-plastic contact analysis of an ultra-high molecular weight polyethylene tibial component based on geometrical measurement from a retrieved knee prosthesis	251–259
Schmidt, M. J.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Schmitt, M.	A novel test method for evaluation of the abrasive wear behaviour of total hip stems at the interface between implant surface and bone cement	223–230
Screen, H. R. C.	An investigation into the effects of the hierarchical structure of tendon fascicles on micromechanical properties	109–119
Shelton, J. C.	An investigation into the effects of the hierarchical structure of tendon fascicles on micromechanical properties	109–119
Sidwell, A.	Effect of twisting hamstring tendon grafts on strength and joint laxity through the range of knee movement	69–77
Sirkett, D. M.	A kinematic model of the wrist based on maximization of joint contact area	349–359
Sitthiseripratip, K.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84

© IMechE 2003

Smutz, W. P.	Elimination of the friction effects in unconfined compression tests of biomaterials and soft tissues	35–40
Stachowiak, G. W.	Temperature prediction in a finite element model for sliding contact analysis of total hip prosthesis	361–370
Steinhauser, E.	A novel test method for evaluation of the abrasive wear behaviour of total hip stems at the interface between implant surface and bone cement	223–230
Sterk, J. C.	Development and experimental validation of a three-dimensional finite element model of the human scapula	127–142
Stoel, B. C.	Evaluation of three pose estimation algorithms for model-based Roentgen stereophotogrammetric analysis	231–238
Stüssi, E.	Prediction of elasticity constants in small biomaterial samples such as bone. A comparison between classical optimization techniques and identification with artificial neural networks	389–405
Su, F-C.	A kinematic method to calculate the workspace of the trapeziometacarpal joint	143–149
Su, F-C.	Muscle forces analysis in the shoulder mechanism during wheelchair propulsion	213–221
Suhendra, N.	Temperature prediction in a finite element model for sliding contact analysis of total hip prosthesis	361–370
Sung, I-H.	Frictional resistance characteristics of a capsule inside the intestine for microendoscope design	193–201
Taylor, W. R.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Teo, E-C.	Prediction of inter-segment stability and osteophyte formation on the multi-segment C2–C7 after unilateral and bilateral facetectomy	183–191
Thompson, M. S.	A comparison of structural and mechanical properties in cancellous bone from the femoral head and acetabulum	425–429
Tongdee, T.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84
Tseng, C-H.	Creative mechanism design for a prosthetic hand	451–459
Turner, H. C.	A method for measuring vertical forces applied to the upper limb during sit-to-stand	461–465
Udofia, I.	Analysis of elastohydrodynamic lubrication in McKee–Farrar metal-on-metal hip joint replacement	27–34
Udofia, I. J.	Contact mechanics analysis of metal-on-metal hip resurfacing prostheses	293–305
Unsworth, A.	Is the wear factor in total joint replacements dependent on the nominal contact stress in ultra-high molecular weight polyethylene contacts?	101–107
Usmani, A. S.	The effect of acetabular cup size on the short-term stability of revision hip arthroplasty: a finite element investigation	239–249
Valstar, E. R.	Evaluation of three pose estimation algorithms for model-based Roentgen stereophotogrammetric analysis	231–238
van der Heim, F. C. T.	Development and experimental validation of a three-dimensional finite element model of the human scapula	127–142
van Keulen, F.	Development and experimental validation of a three-dimensional finite element model of the human scapula	127–142
Van Oosterwyck, H.	Numerical analysis of bone adaptation around an oral implant due to overload stress	407–415
Vander Sloten, J.	Morphology of the radial head: a reverse engineering based evaluation using three-dimensional anatomical data of radial bone	79–84
Vandere Sloten, J.	Numerical analysis of bone adaptation around an oral implant due to overload stress	407–415
Vassiliou, K.	Is the wear factor in total joint replacements dependent on the nominal contact stress in ultra-high molecular weight polyethylene contacts?	101–107
Verdonschot, .	Effect of joint conformity on glenoid component fixation in total shoulder arthroplasty	339–347
Viceconti, M.	A procedure and criterion for bone cement fracture toughness testing	445–450
Visvanathan, K.	Effect of foot sole hardness, thickness and footwear on foot pressure distribution parameters in diabetic neuropathy	431–443
Wang, F. C.	Steady-state elastohydrodynamic lubrication analysis of a metal-on-metal hip implant employing a metallic cup with an ultra-high molecular weight polyethylene backing	261–270
Wang, F. C.	A general elastohydrodynamic lubrication analysis of artificial hip joints employing a compliant layered socket under steady state rotation	283–2912
Warner, M. D.	Investigating the effect of remodelling signal type on the finite element based predictions of bone remodelling around the thrust plate prosthesis: a patient-specific comparison	417–424
Weir, N. A.	Degradation of poly-L-lactide: Part 1: *in vitro* and *in vivo* physiological temperature degradation	307–319
Weir, N. A.	Degradation of poly-L-lactide: Part 2: increased temperature accelerated degradation	321–330
Wilcox, R. K.	The biomechanics of vertebroplasty: a review	1–10
Wild, P.	Effect of twisting hamstring tendon grafts on strength and joint laxity through the range of knee movement	69–77
Wilson, D.	Effect of twisting hamstring tendon grafts on strength and joint laxity through the range of knee movement	69–77
Wright, M. T.	A flexible digit with tactile feedback for invasive clinical applications	151–157
Wu, J. Z.	Elimination of the friction effects in unconfined compression tests of biomaterials and soft tissues	35–40
Wu, H-W.	Muscle forces analysis in the shoulder mechanism during wheelchair propulsion	213–221
Wu, L-L.	Creative mechanism design for a prosthetic hand	451–459
Yahia, F. B.	A finite element rheological model for polymethylmethacrylate: analysis of the cement delivery in vertebroplasty	331–338
Yate, R. M.	A method for measuring vertical forces applied to the upper limb during sit-to-stand	461–465
Yew, A.	Analysis of elastohydrodynamic lubrication in McKee–Farrar metal-on-metal hip joint replacement	27–34
Yew, A.	Contact mechanics analysis of metal-on-metal hip resurfacing prostheses	293–305
Zhang, Q-H.	Prediction of inter-segment stability and osteophyte formation on the multi-segment C2–C7 after unilateral and bilateral facetectomy	183–191

© IMechE 2003